



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/688,274

10/17/2003

Vernon R. Brethour

ALER1250

3777

44654 7590 07/05/2007
SPRINKLE IP LAW GROUP
1301 W. 25TH STREET
SUITE 408
AUSTIN, TX 78705

EXAMINER

AKBAR, MUHAMMAD A

ART UNIT

PAPER NUMBER

2618

MAIL DATE

DELIVERY MODE

07/05/2007

PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 10/688,274	Applicant(s) BRETHOUR ET AL.	
	Examiner Muhammad Akbar	Art Unit 2618	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 17 October 2003.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-84 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-84 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 17 October 2003 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date <u>10/07/2004</u> . | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Claim Rejections - 35 USC § 101

1. 35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

2. Claims 29-56 are rejected under 35 U.S.C. 101 because the claim invention is directed to non-statutory subject matter. In claim 29-56 as cited in the preamble "A tangible electronic media, comprising a program for...including instructions translatable". Thus, a tangible electronic media and program would reasonable be interpreted by one of ordinary skill in the art as descriptive material, per se and program per se is non-statutory.

Claim Rejections - 35 USC § 103

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

4. The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

Art Unit: 2618

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

5. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

6. Claims 1-84 are rejected under 35 U.S.C. 103(a) as being unpatentable over Sugar et al (U.S. Pub. No. 2002/0061031 A1) and in view of Shellhammer et al (U.S. Patent No. 7,039,358 B1).

Re claim 1, Sugar discloses a method comprising mitigating interference between piconets (Bluetooth enable multiple protocol device (PMD) communicate with node Na (which includes Bluetooth enable device 14 and 22 using first protocol) i.e. first piconet and PMD communicate with node Nb (which includes Bluetooth enable device 16 and 20 using second protocol) i.e. second piconet (see title, fig.1,7 ,para[0108], [0042],[0066]) including:

detecting interference between Bluetooth enable communication device i.e. first piconet (Na) and second piconet (Nb) by the detector (297 of fig.12A) of MPD (see fig.1,2 and para[0080],[0088]); and hold -off (ceasing) transmitting protocol signal A (from first piconet Na) on first set band wherein and first piconet (Na) hold off (ceases) transmission by at least one of a plurality of devices with multiple protocol device (MPD) (since Na is comprises with two device 14 and 22, see fig. 1,7) on first set of band and Bluetooth enable device Nb i.e. second piconet can continue to use first set of frequency band (see fig.1,7 and para [0007],[0058]) (since two frequency band are same and coexisting and node Nb (second piconet) can continue transmit to use first frequency band through frequency hop protocol).

But Sugar does not disclose explicitly forming two piconet associated with plurality of device. However, Shellhammer teaches techniques for frequency coordination between two Bluetooth enable IEEE 802.11 network protocol (same field of endeavor) wherein reducing (mitigating) and detecting interference between piconet (280) and piconet (290) (see fig.1, col.4 lines 29-34,col.7 lines 10-15); and Shellhammer further teaches piconet (280) and second piconet (290) are associated with plurality of devices (see fig.1, device 160,170,180,190,200,210) and using same frequency band which is comprises two or more frequency sub bands (col.3 lines 25-30).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the mitigating and detecting interference between piconets and hold off transmission one of the device (as taught by Sugar) by incorporating piconet (280 and 290) with multiple devices and used same frequency

Art Unit: 2618

band (as taught by Shellhammer) to improve reducing interference between Bluetooth enable multiple devices in a piconet communication protocol.

Re claim 2, as discussed above with respect to claim 1, Sugar further discloses hold-off (ceasing) transmitting protocol signal B (from Bluetooth enable piconet Nb) wherein Bluetooth enable piconet Nb (i.e. second piconet) hold off (ceases) transmission by at least one of another plurality of devices (Nb is consisting Bluetooth enable device 16 and 20 see fig. 1 and para[0042]) on a second set of band (para [007]) and first piconet Na continue to use second set of frequency band (see fig.1,7 and para [0007],[0056],[0058]) (since Bluetooth WLAN network operating one or more frequency hopping communication protocol with co-existing same frequency band i.e. two frequency band are same and Nb (second piconet) can continue transmit to use second frequency band through frequency hop protocol, para[0066])

Re claim 3, as discussed above with respect to claim 1, Sugar further discloses stopped (ceasing) transmission on the first set of bands is done for a short duration which is pre identified by DURID i.e. predetermined time period (see fig.15 and para [0086],[0091])

Re claim 4, as discussed above with respect to claim 3, Sugar further discloses the first set of bands (Sa) and the second set of bands (Sb) are substantially orthogonal (see fig.4).

Re claim 5, as discussed above with respect to claim 4, Sugar further discloses the first set of bands and the second sets of bands substantially encompass a time division duplex format i.e. time coded frequency spectrum (see fig. 5A and para [0050]).

Re claim 6, as discussed above with respect to claim 1, Sugar further discloses monitoring the first set of bands for activity (measure network load, slot duration, activity of bands), wherein the first set of bands is monitored by the multiple protocol device (MPD) with Bluetooth enable device Na i.e. first piconet (see para [0142])

Re claim 7, as discussed above with respect to claim 6, Sugar further discloses transmit again (i.e. resuming transmission) by at least one of the plurality of devices (Na and Nb) on one or more of the sub bands in the first set of bands when network is detected idle (i.e. no activity) on one or more bands within the first set of bands (see fig.7,8 para[0094];[0095]).

Re claim(s) 8,9,10, as discussed above with respect to claim 1, Sugar further discloses detecting interference includes evaluating an bit error rate (see fig.2 and para[0059]); and bit error rate and the evaluation is done at the physical layer (see fig.2 item 180-184 and para [0073]); and bit error rate is a packet error rate and the evaluation is done at the medium access control layer(MAC)(see fig.2 and para[0084]) (IEEE 802.11 protocol and WLAN are medium access control layer)

Re claim(s) 11,12,13, as discussed above with respect to claim 1, Sugar furthermore teaches attempting to mitigate interference through the use of time division multiple access when interference is detected (see fig. 2 and para [0067]); and processing further (like modulating, converting interference signal) i.e. characterizing interference upon interference is detected by the detector (120 of fig.2); and sugar further teaches process of the interference signal i.e. characterizing includes channel assessment is done by the physical layer (see fig.2 and para[0073]).

Re claim 14, Sugar discloses a method comprising mitigating interference between piconets (Bluetooth enable multiple protocol device (PMD) communicate with node Na (which includes Bluetooth enable device 14 and 22 using first protocol) i.e. first piconet and PMD communicate with node Nb (which includes Bluetooth enable device 16 and 20 using second protocol) i.e. second piconet (see title, fig.1,7 ,para[0108], [0042],[0066]) including:

detecting interference between Bluetooth enable communication device i.e. first piconet (Na) and second piconet (Nb) by the detector (297 of fig.12A) of MPD (see fig.1,2 and para[0080],[0088]);communicating between the first piconet (Na) and the second piconet (Nb) by using first protocol and second protocol through multiple device protocol with WLAN wherein the communication includes establishing a first set of bands and a second set of bands (see fig.1,3,4 and para [007]) (since WLAN protocol have two or more frequency hopping communication protocol coexisting with one or more same frequency band); and hold -off (ceasing) transmitting protocol signal A

(from first piconet Na) on first set band wherein and first piconet (Na) hold off (ceases) transmission by at least one of a plurality of devices with multiple protocol device (MPD) (since Na is comprises with two device 14 and 22, see fig. 1,7) on first set of band and Bluetooth enable device Nb i.e. second piconet can continue to use first set of frequency band (see fig.1,7 and para [0007],[0058]) (since two frequency band are same and coexisting and node Nb (second piconet) can continue transmit to use first frequency band through frequency hop protocol).

But Sugar does not disclose explicitly forming two piconet associated with plurality of device. However, Shellhammer teaches techniques for frequency coordination between two Bluetooth enable IEEE 802.11 network protocol (same field of endeavor) wherein reducing (mitigating) and detecting interference between piconet (280) and piconet (290) (see fig.1, col.4 lines 29-34,col.7 lines 10-15); and Shellhammer further teaches piconet (280) and second piconet (290) are associated with plurality of devices (see fig.1, device 160,170,180,190,200,210) and using same frequency band which is comprises two or more frequency sub bands (col.3 lines 25-30).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the mitigating and detecting interference between piconets and hold off transmission one of the device (as taught by Sugar) by incorporating piconet (280 and 290) with multiple devices and used same frequency band (as taught by Shellhammer) to improve reducing interference between Bluetooth enable multiple devices in a piconet communication protocol.

Re claim 15 , as discussed above with respect to claim 14, Sugar further discloses hold -off (ceasing) transmitting protocol signal B (from Bluetooth enable piconet Nb) wherein Bluetooth enable piconet Nb (i.e. second piconet) hold off (ceases) transmission by at least one of another plurality of devices (Nb is consisting Bluetooth enable device 16 and 20 see fig. 1 and para[0042]) on a second set of band (para [007]) and first piconet Na continue to use second set of frequency band (see fig.1,7 and para [0007],[0056],[0058]) (since Bluetooth WLAN network operating one or more frequency hoping communication protocol with co-existing same frequency band i.e. two frequency band are same and Nb (second piconet) can continue transmit to use second frequency band through frequency hop protocol, para[0066])

Re claim 16, as discussed above with respect to claim 14, Sugar further discloses stopped (ceasing) transmission on the first set of bands is done for a short duration which is pre identified by DURID i.e. predetermined time period (see fig.15 and para [0086],[0091])

Re claim 17,18, as discussed above with respect to claim 14, Sugar furthermore teaches first piconet (Na) keeping an activity record i.e. history with PMD (PMD has processor, controller wherein keep record of the ACK message, transmitting protocol and duration of frequency hopping) and first set of band is used in the first piconet (Na) (see fig.2,7 and para [007],[0094]) (first piconet used first frequency band and need

waits one short interference space period from the end of the transmitting message, thus first piconet need keep tracking history of frequency band)

Re claim 19, as discussed above with respect to claim 18, Sugar further discloses the first set of bands (Sa) and the second set of bands (Sb) are substantially orthogonal (see fig.4).

Re claim 20, as discussed above with respect to claim 19, Sugar further discloses the first set of bands and the second sets of bands substantially encompass a time division duplex format i.e. time coded frequency spectrum (see fig. 5A and para [0050]).

Re claim 21, as discussed above with respect to claim 14, Sugar further discloses monitoring the first set of bands for activity (measure network load, slot duration, activity of bands), wherein the first set of bands is monitored by the multiple protocol device (MPD) with Bluetooth enable device Na i.e. first piconet (see para [0142])

Re claim 22, as discussed above with respect to claim 21, Sugar further discloses transmit again (i.e. resuming transmission) by at least one of the plurality of devices (Na and Nb) on one or more of the sub bands in the first set of bands when

network is detected idle (i.e. no activity) on one or more bands within the first set of bands (see fig.7,8 para[0094];[0095]).

Re claim(s) 23,24,25, as discussed above with respect to claim 14, Sugar further discloses detecting interference includes evaluating an bit error rate (see fig.2 and para[0059]); and bit error rate and the evaluation is done at the physical layer (see fig.2 item 180-184 and para [0073]); and bit error rate is a packet error rate and the evaluation is done at the medium access control layer(MAC)(see fig.2 and para[0084]) (IEEE 802.11 protocol and WLAN are medium access control layer)

Re claim(s) 26,27,28, as discussed above with respect to claim 14, Sugar furthermore teaches attempting to mitigate interference through the use of time division multiple access when interference is detected (see fig. 2 and para [0067]); and processing further (like modulating, converting interference signal) i.e. characterizing interference upon interference is detected by the detector (120 of fig.2); and sugar further teaches process of the interference signal i.e. characterizing includes channel assessment is done by the physical layer (see fig.2 and para[0073]).

Re claim 29, Sugar discloses Bluetooth enable wireless communication comprises processor which can be configured or programmed to perform software instruction for mitigating interference between piconets (Bluetooth enable multiple protocol device (PMD) communicate with node Na (which includes Bluetooth enable

device 14 and 22 using first protocol) i.e. first piconet and PMD communicate with node Nb (which includes Bluetooth enable device 16 and 20 using second protocol) i.e. second piconet (see title, fig.1,7 ,para[0108], [0042],[0066]) and steps including:

detecting interference between Bluetooth enable communication device i.e. first piconet (Na) and second piconet (Nb) by the detector (297 of fig.12A) of MPD (see fig.1,2 and para[0080],[0088]);and hold -off (ceasing) transmitting protocol signal A (from first piconet Na) on first set band wherein and first piconet (Na) hold off (ceases) transmission by at least one of a plurality of devices with multiple protocol device (MPD) (since Na is comprises with two device 14 and 22, see fig. 1,7) on first set of band and Bluetooth enable device Nb i.e. second piconet can continue to use first set of frequency band (see fig.1,7 and para [0007],[0058]) (since two frequency band are same and coexisting and node Nb (second piconet) can continue transmit to use first frequency band through frequency hop protocol).

But Sugar does not disclose explicitly forming two piconet associated with plurality of device. However, Shellhammer teaches techniques for frequency coordination between two Bluetooth enable IEEE 802.11 network protocol (same field of endeavor) wherein reducing (mitigating) and detecting interference between piconet (280) and piconet (290) (see fig.1, col.4 lines 29-34,col.7 lines 10-15); and Shellhammer further teaches piconet (280) and second piconet (290) are associated with plurality of devices (see fig.1, device 160,170,180,190,200,210) and using same frequency band which is comprises two or more frequency sub bands (col.3 lines 25-30).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the mitigating and detecting interference between piconets and hold off transmission one of the device (as taught by Sugar) by incorporating piconet (280 and 290) with multiple devices and used same frequency band (as taught by Shellhammer) to improve reducing interference between Bluetooth enable multiple devices in a piconet communication protocol.

Re claim 30, as discussed above with respect to claim 29, Sugar further discloses hold -off (ceasing) transmitting protocol signal B (from Bluetooth enable piconet Nb) wherein Bluetooth enable piconet Nb (i.e. second piconet) hold off (ceases) transmission by at least one of another plurality of devices (Nb is consisting Bluetooth enable device 16 and 20 see fig. 1 and para[0042]) on a second set of band (para [007]) and first piconet Na continue to use second set of frequency band (see fig.1,7 and para [0007],[0056],[0058]) (since Bluetooth WLAN network operating one or more frequency hoping communication protocol with co-existing same frequency band i.e. two frequency band are same and Nb (second piconet) can continue transmit to use second frequency band through frequency hop protocol, para[0066])

Re claim 31, as discussed above with respect to claim 29, Sugar further discloses stopped (ceasing) transmission on the first set of bands is done for a short duration which is pre identified by DURID i.e. predetermined time period (see fig.15 and para [0086],[0091])

Re claim 32, as discussed above with respect to claim 31, Sugar further discloses the first set of bands (Sa) and the second set of bands (Sb) are substantially orthogonal (see fig.4).

Re claim 33, as discussed above with respect to claim 32, Sugar further discloses the first set of bands and the second sets of bands substantially encompass a time division duplex format i.e. time coded frequency spectrum (see fig. 5A and para [0050]).

Re claim 34, as discussed above with respect to claim 29, Sugar further discloses monitoring the first set of bands for activity (measure network load, slot duration, activity of bands), wherein the first set of bands is monitored by the multiple protocol device (MPD) with Bluetooth enable device Na i.e. first piconet (see para [0142])

Re claim 35, as discussed above with respect to claim 34, Sugar further discloses transmit again (i.e. resuming transmission) by at least one of the plurality of devices (Na and Nb) on one or more of the sub bands in the first set of bands when network is detected idle (i.e. no activity) on one or more bands within the first set of bands (see fig.7,8 para[0094];[0095]).

Re claim(s) 36,37,38, as discussed above with respect to claim 29, Sugar further discloses detecting interference includes evaluating an bit error rate (see fig.2 and para[0059]); and bit error rate and the evaluation is done at the physical layer (see fig.2 item 180-184 and para [0073]); and bit error rate is a packet error rate and the evaluation is done at the medium access control layer(MAC)(see fig.2 and para[0084]) (IEEE 802.11 protocol and WLAN are medium access control layer)

Re claim(s) 39,40,41, as discussed above with respect to claim 29, Sugar furthermore teaches attempting to mitigate interference through the use of time division multiple access when interference is detected (see fig. 2 and para [0067]); and processing further (like modulating, converting interference signal) i.e. characterizing interference upon interference is detected by the detector (120 of fig.2); and sugar further teaches process of the interference signal i.e. characterizing includes channel assessment is done by the physical layer (see fig.2 and para[0073]).

Re claim 42, Sugar discloses Bluetooth enable wireless communication comprises processor which can be configured or programmed to perform software instruction for mitigating interference between piconets (Bluetooth enable multiple protocol device (PMD) communicate with node Na (which includes Bluetooth enable device 14 and 22 using first protocol) i.e. first piconet and PMD communicate with node Nb (which includes Bluetooth enable device 16 and 20 using second protocol) i.e. second piconet (see title, fig.1,7 ,para[0108], [0042],[0066]) and steps including:

Art Unit: 2618

detecting interference between Bluetooth enable communication device i.e. first piconet (Na) and second piconet (Nb) by the detector (297 of fig.12A) of MPD (see fig.1,2 and para[0080],[0088]);communicating between the first piconet (Na) and the second piconet (Nb) by using first protocol and second protocol through multiple device protocol with WLAN wherein the communication includes establishing a first set of bands and a second set of bands (see fig.1,3,4 and para [007]) (since WLAN protocol have two or more frequency hopping communication protocol coexisting with one or more same frequency band); and hold -off (ceasing) transmitting protocol signal A (from first pioconet Na) on first set band wherein and first piconet (Na) hold off (ceases) transmission by at least one of a plurality of devices with multiple protocol device (MPD) (since Na is comprises with two device 14 and 22, see fig. 1,7) on first set of band and Bluetooth enable device Nb i.e. second piconet can continue to use first set of frequency band (see fig.1,7 and para [0007],[0058]) (since two frequency band are same and coexisting and node Nb (second piconet) can continue transmit to use first frequency band through frequency hop protocol).

But Sugar does not disclose explicitly forming two piconet associated with plurality of device. However, Shellhammer teaches techniques for frequency coordination between two Bluetooth enable IEEE 802.11 network protocol (same field of endeavor) wherein reducing (mitigating) and detecting interference between piconet (280) and piconet (290) (see fig.1, col.4 lines 29-34,col.7 lines 10-15); and Shellhammer further teaches piconet (280) and second piconet (290) are associated with plurality of

devices (see fig.1, device 160,170,180,190,200,210) and using same frequency band which is comprises two or more frequency sub bands (col.3 lines 25-30).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the mitigating and detecting interference between piconets and hold off transmission one of the device (as taught by Sugar) by incorporating piconet (280 and 290) with multiple devices and used same frequency band (as taught by Shellhammer) to improve reducing interference between Bluetooth enable multiple devices in a piconet communication protocol.

Re claim 43, as discussed above with respect to claim 42, Sugar further discloses hold -off (ceasing) transmitting protocol signal B (from Bluetooth enable piconet Nb) wherein Bluetooth enable piconet Nb (i.e. second piconet) hold off (ceases) transmission by at least one of another plurality of devices (Nb is consisting Bluetooth enable device 16 and 20 see fig. 1 and para[0042]) on a second set of band (para [007]) and first piconet Na continue to use second set of frequency band (see fig.1,7 and para [0007],[0056],[0058]) (since Bluetooth WLAN network operating one or more frequency hopping communication protocol with co-existing same frequency band i.e. two frequency band are same and Nb (second piconet) can continue transmit to use second frequency band through frequency hop protocol, para[0066])

Re claim 44, as discussed above with respect to claim 42, Sugar further discloses stopped (ceasing) transmission on the first set of bands is done for a short

duration which is pre identified by DURID i.e. predetermined time period (see fig.15 and para [0086],[0091])

Re claim 45,46, as discussed above with respect to claim 42, Sugar furthermore teaches first piconet (Na) keeping an activity record i.e. history with PMD (PMD has processor, controller wherein keep record of the ACK message, transmitting protocol and duration of frequency hopping) and first set of band is used in the first piconet (Na) (see fig.2,7 and para [007],[0094]) (first piconet used first frequency band and need waits one short interference space period from the end of the transmitting message,thus first piconet need keep tracking history of frequency band)

Re claim 47, as discussed above with respect to claim 46, Sugar further discloses the first set of bands (Sa) and the second set of bands (Sb) are substantially orthogonal (see fig.4).

Re claim 48, as discussed above with respect to claim 47, Sugar further discloses the first set of bands and the second sets of bands substantially encompass a time division duplex format i.e. time coded frequency spectrum (see fig. 5A and para [0050]).

Re claim 49, as discussed above with respect to claim 42, Sugar further discloses monitoring the first set of bands for activity (measure network load, slot

duration, activity of bands), wherein the first set of bands is monitored by the multiple protocol device (MPD) with Bluetooth enable device Na i.e. first piconet (see para [0142])

Re claim 50, as discussed above with respect to claim 49, Sugar further discloses transmit again (i.e. resuming transmission) by at least one of the plurality of devices (Na and Nb) on one or more of the sub bands in the first set of bands when network is detected idle (i.e. no activity) on one or more bands within the first set of bands (see fig.7,8 para[0094];[0095]).

Re claim(s) 51,52,53, as discussed above with respect to claim 42, Sugar further discloses detecting interference includes evaluating an bit error rate (see fig.2 and para[0059]); and bit error rate and the evaluation is done at the physical layer (see fig.2 item 180-184 and para [0073]); and bit error rate is a packet error rate and the evaluation is done at the medium access control layer(MAC)(see fig.2 and para[0084]) (IEEE 802.11 protocol and WLAN are medium access control layer)

Re claim(s) 54,55,56, as discussed above with respect to claim 42, Sugar furthermore teaches attempting to mitigate interference through the use of time division multiple access when interference is detected (see fig. 2 and para [0067]); and processing further (like modulating, converting interference signal) i.e. characterizing interference upon interference is detected by the detector (120 of fig.2); and sugar

further teaches process of the interference signal i.e. characterizing includes channel assessment is done by the physical layer (see fig.2 and para[0073]).

Re claim 57, Sugar discloses an apparatus comprising mitigating interference between piconets (Bluetooth enable multiple protocol device (PMD) communicate with node Na (which includes Bluetooth enable device 14 and 22 using first protocol) i.e. first piconet and PMD communicate with node Nb (which includes Bluetooth enable device 16 and 20 using second protocol) i.e. second piconet (see title, fig.1,7 ,para[0108], [0042],[0066]) including:

detecting interference between Bluetooth enable communication device i.e. first piconet (Na) and second piconet (Nb) by the detector (297 of fig.12A) of MPD (see fig.1,2 and para[0080],[0088]); and hold -off (ceasing) transmitting protocol signal A (from first piconet Na) on first set band wherein and first piconet (Na) hold off (ceases) transmission by at least one of a plurality of devices with multiple protocol device (MPD) (since Na is comprises with two device 14 and 22, see fig. 1,7) on first set of band and Bluetooth enable device Nb i.e. second piconet can continue to use first set of frequency band (see fig.1,7 and para [0007],[0058]) (since two frequency band are same and coexisting and node Nb (second piconet) can continue transmit to use first frequency band through frequency hop protocol).

But Sugar does not disclose explicitly forming two piconet associated with plurality of device. However, Shellhammer teaches techniques for frequency coordination between two Bluetooth enable IEEE 802.11 network protocol (same field of

endeavor) wherein reducing (mitigating) and detecting interference between piconet (280) and piconet (290) (see fig.1, col.4 lines 29-34,col.7 lines 10-15); and Shellhammer further teaches piconet (280) and second piconet (290) are associated with plurality of devices (see fig.1, device 160,170,180,190,200,210) and using same frequency band which is comprises two or more frequency sub bands (col.3 lines 25-30).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the mitigating and detecting interference between piconets and hold off transmission one of the device (as taught by Sugar) by incorporating piconet (280 and 290) with multiple devices and used same frequency band (as taught by Shellhammer) to improve reducing interference between Bluetooth enable multiple devices in a piconet communication protocol.

Re claim 58, as discussed above with respect to claim 57; Sugar further discloses hold -off (ceasing) transmitting protocol signal B (from Bluetooth enable piconet Nb) wherein Bluetooth enable piconet Nb (i.e. second piconet) hold off (ceases) transmission by at least one of another plurality of devices (Nb is consisting Bluetooth enable device 16 and 20 see fig. 1 and para[0042]) on a second set of band (para [007]) and first piconet Na continue to use second set of frequency band (see fig.1,7 and para [0007],[0056],[0058]) (since Bluetooth WLAN network operating one or more frequency hoping communication protocol with co-existing same frequency band i.e. two frequency band are same and Nb (second piconet) can continue transmit to use second frequency

Art Unit: 2618

band through frequency hop protocol, para[0066])

Re claim 59, as discussed above with respect to claim 57, Sugar further discloses stopped (ceasing) transmission on the first set of bands is done for a short duration which is pre identified by DURID i.e. predetermined time period (see fig.15 and para [0086],[0091])

Re claim 60, as discussed above with respect to claim 59, Sugar further discloses the first set of bands (Sa) and the second set of bands (Sb) are substantially orthogonal (see fig.4).

Re claim 61, as discussed above with respect to claim 60, Sugar further discloses the first set of bands and the second sets of bands substantially encompass a time division duplex format i.e. time coded frequency spectrum (see fig. 5A and para [0050]).

Re claim 62, as discussed above with respect to claim 57, Sugar further discloses monitoring the first set of bands for activity (measure network load, slot duration, activity of bands), wherein the first set of bands is monitored by the multiple protocol device (MPD) with Bluetooth enable device Na i.e. first piconet (see para [0142])

Art Unit: 2618

Re claim 63, as discussed above with respect to claim 62, Sugar further discloses transmit again (i.e. resuming transmission) by at least one of the plurality of devices (Na and Nb) on one or more of the sub bands in the first set of bands when network is detected idle (i.e. no activity) on one or more bands within the first set of bands (see fig.7,8 para[0094];[0095]).

Re claim(s) 64,65,66, as discussed above with respect to claim 57, Sugar further discloses detecting interference includes evaluating an bit error rate (see fig.2 and para[0059]); and bit error rate and the evaluation is done at the physical layer (see fig.2 item 180-184 and para [0073]); and bit error rate is a packet error rate and the evaluation is done at the medium access control layer(MAC)(see fig.2 and para[0084]) (IEEE 802.11 protocol and WLAN are medium access control layer)

Re claim(s) 67,68,69, as discussed above with respect to claim 57, Sugar furthermore teaches attempting to mitigate interference through the use of time division multiple access when interference is detected (see fig. 2 and para [0067]); and processing further (like modulating, converting interference signal) i.e. characterizing interference upon interference is detected by the detector (120 of fig.2); and sugar further teaches process of the interference signal i.e. characterizing includes channel assessment is done by the physical layer (see fig.2 and para[0073]).

Re claim 70, Sugar discloses an apparatus comprising a first piconet (Na) mitigating interference between piconets (Bluetooth enable multiple protocol device (PMD) communicate with node Na (which includes Bluetooth enable device 14 and 22 using first protocol) i.e. first piconet and PMD communicate with node Nb (which includes Bluetooth enable device 16 and 20 using second protocol) i.e. second piconet (see title, fig.1,7 ,para[0108], [0042],[0066]) including:

detecting interference between Bluetooth enable communication device i.e. first piconet (Na) and second piconet (Nb) by the detector (297 of fig.12A) of MPD (see fig.1,2 and para[0080],[0088]);and hold -off (ceasing) transmitting protocol signal A (from first piconet Na) on first set band wherein and first piconet (Na) hold off (ceases) transmission by at least one of a plurality of devices with multiple protocol device (MPD) (since Na is comprises with two device 14 and 22, see fig. 1,7) on first set of band and Bluetooth enable device Nb i.e. second piconet can continue to use first set of frequency band (see fig.1,7 and para [0007],[0058]) (since two frequency band are same and coexisting and node Nb (second piconet) can continue transmit to use first frequency band through frequency hop protocol).

But Sugar does not disclose explicitly forming two piconet associated with plurality of device. However, Shellhammer teaches techniques for frequency coordination between two Bluetooth enable IEEE 802.11 network protocol (same field of endeavor) wherein reducing (mitigating) and detecting interference between piconet (280) and piconet (290) (see fig.1, col.4 lines 29-34,col.7 lines 10-15); and Shellhammer further teaches piconet (280) and second piconet (290) are associated with plurality of

devices (see fig.1, device 160,170,180,190,200,210) and using same frequency band which is comprises two or more frequency sub bands (col.3 lines 25-30).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the mitigating and detecting interference between piconets and hold off transmission one of the device (as taught by Sugar) by incorporating piconet (280 and 290) with multiple devices and used same frequency band (as taught by Shellhammer) to improve reducing interference between Bluetooth enable multiple devices in a piconet communication protocol.

Re claim 71, as discussed above with respect to claim 70, Sugar further discloses hold -off (ceasing) transmitting protocol signal B (from Bluetooth enable piconet Nb) wherein Bluetooth enable piconet Nb (i.e. second piconet) hold off (ceases) transmission by at least one of another plurality of devices (Nb is consisting Bluetooth enable device 16 and 20 see fig. 1 and para[0042]) on a second set of band (para [007]) and first piconet Na continue to use second set of frequency band (see fig.1,7 and para [0007],[0056],[0058]) (since Bluetooth WLAN network operating one or more frequency hoping communication protocol with co-existing same frequency band i.e. two frequency band are same and Nb (second piconet) can continue transmit to use second frequency band through frequency hop protocol, para[0066])

Re claim 72, as discussed above with respect to claim 70, Sugar further discloses stopped (ceasing) transmission on the first set of bands is done for a short

Art Unit: 2618

duration which is pre identified by DURID i.e. predetermined time period (see fig.15 and para [0086],[0091])

Re claim 73,74, as discussed above with respect to claim 70, Sugar furthermore teaches first piconet (Na) keeping an activity record i.e. history with PMD (PMD has processor, controller wherein keep record of the ACK message, transmitting protocol and duration of frequency hopping) and first set of band is used in the first piconet (Na) (see fig.2,7 and para [007],[0094]) (first piconet used first frequency band and need waits one short interference space period from the end of the transmitting message, thus first piconet need keep tracking history of frequency band)

Re claim 75, as discussed above with respect to claim 74, Sugar further discloses the first set of bands (Sa) and the second set of bands (Sb) are substantially orthogonal (see fig.4).

Re claim 76, as discussed above with respect to claim 75, Sugar further discloses the first set of bands and the second sets of bands substantially encompass a time division duplex format i.e. time coded frequency spectrum (see fig. 5A and para [0050]).

Re claim 77, as discussed above with respect to claim 70, Sugar further discloses monitoring the first set of bands for activity (measure network load, slot

duration, activity of bands), wherein the first set of bands is monitored by the multiple protocol device (MPD) with Bluetooth enable device Na i.e. first piconet (see para [0142])

Re claim 78, as discussed above with respect to claim 77, Sugar further discloses transmit again (i.e. resuming transmission) by at least one of the plurality of devices (Na and Nb) on one or more of the sub bands in the first set of bands when network is detected idle (i.e. no activity) on one or more bands within the first set of bands (see fig.7,8 para[0094];[0095]).

Re claim(s) 79,80,81, as discussed above with respect to claim 70, Sugar further discloses detecting interference includes evaluating an bit error rate (see fig.2 and para[0059]); and bit error rate and the evaluation is done at the physical layer (see fig.2 item 180-184 and para [0073]); and bit error rate is a packet error rate and the evaluation is done at the medium access control layer(MAC)(see fig.2 and para[0084]) (IEEE 802.11 protocol and WLAN are medium access control layer)

Re claim(s) 82,83,84, as discussed above with respect to claim 70, Sugar furthermore teaches attempting to mitigate interference through the use of time division multiple access when interference is detected (see fig. 2 and para [0067]); and processing further (like modulating, converting interference signal) i.e. characterizing interference upon interference is detected by the detector (120 of fig.2); and sugar

Art Unit: 2618

further teaches process of the interference signal i.e. characterizing includes channel assessment is done by the physical layer (see fig.2 and para[0073]).

Conclusion

7. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure (7.96)

The following patent are cited to further show the state of the art with respect to clips and bookmarks in general:

U.S. Patent No. 6,711,380 to Callaway, Jr: teaches method and apparatus for reducing interference effect caused by microwave sources using piconet network.

U.S. Patent No. 7,126,937 to Crosbie et al teaches methods and system for clock synchronization across wireless network using piconet.

U.S. PG. Pub. 2006/0183423 A1 to Johansson et al teaches flexible inter-network communication scheduling uses piconet.

8. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Muhammad Akbar whose telephone number is (571)-270-1218. The examiner can normally be reached on Monday- Thursday (7:30 A.M.- 5:00P.M). If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Edan Orgad can be reached on 571-272-7884. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2618

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

MA

EDAN ORGAD
PRIMARY PATENT EXAMINER

Edan Orgad 6/29/07